



PAR12X20H-IP [-WH]

OUTDOOR PRO PAR

EVENT
LIGHTING

PARCANS



Photometrics

Light Source:	12x 20W RGBWA+UV 6 in 1 LED
Beam Angle:	22°
Output:	12,700 lux @ 2.0 m full on
PWM:	1,240 Hz
Led lifespan:	50,000 hours

Effects

Dimming:	5 x 16-bit Dimming Curves
Strobe:	1~30 Hz

Power

Power consumption:	250W Max
Input Voltage:	100V~240 V AC, 50/60Hz
Connection:	True1 in/out

Control

Control Protocol:	DMX512
DMX Channels:	1 / 2 / 3 / 4W / 4A / 6 / 8 / 12 / 14
Interface:	5-pin XLR in / out
Operational Modes:	DMX, WDMX, auto run, sound active, master/slave, manual colour control, static colour control
Display	4-button LCD control panel

Housing

Materials:	Die-cast aluminium, matte black or white finish
Dimensions:	299 x 217 x 333 mm
Cooling:	Fanless Cooling
IP rating:	IP65
Net Weight:	3.2kg
Rigging:	1x Omega bracket with 1/4 turn quick locks

Optional Accessories

PAR12X20HIPBD [-WH]

Rotatable Barn
Doors with
base, gel frame,
frost and safety
loop



PAR12GELFR

Gel frame for PAR12H/Q/VW



PAR12FROST

Frost filter for PAR12H/Q/VW



Lux @ 22°

	1.0m	2.0m	3.0m	4.0m	5.0m
R	8,000	2,000	981	557	411
G	12,680	3,480	1,630	963	670
B	2,600	660	350	195	142
W	16,800	4,730	2,080	1,255	883
A	13,300	3,510	1,630	961	662
U	510	170	92	44	31
Full	48,000	12,700	5,790	3,370	2,340

Road Case (Optional)

PAR12X20HIPCASE

Road Case to suit 6
units of PAR12X20H-IP
Parcans



PAR12X20H-IP [-WH]