

CYC250C

CYCLORAMA FIXTURE WITH 210W
5-IN-1 RGBIL LEDS



Photometrics	
Light Source:	210W RGBIL 5-in-1 LED
Colours:	Red, Green, Blue, Indigo, Lime - 5 Line Colour Mixing
Colour Temperature:	2,700K - 6,500K
Output:	4,850 lux @ 1m / 3" at 75°
Led lifespan:	50,000 hours
CRI:	>95Ra
Effects	
Dimming:	0~100% Linear
Strobe	1~25 Hz
Control	
Control Protocol	DMX512, Auto, Sound Active, Master/Slave
DMX Channels:	7
Interface:	3-Pin XLR In/Out
Display:	OLED Display (4 Button Control)
Power	
Power Consumption:	250W Max.
Input Voltage:	100~240 V AC, 50/60 Hz
Connection:	PowerCon In/Out
Housing	
Materials:	Aluminium Alloy with Matte Black Finish
Dimensions:	263 x 226 x 284mm / 10.4" x 8.9" x 11.2"
Cooling:	Fanless Cooling
IP Rating:	IP20
Net Weight:	9.5 kg / 20.9 lbs

Lux @75°		CYC250C			
Distance From Source	1m / 3'3"	2m / 6'7"	3m / 9'10"	4m / 13'2"	
Red	1,182	258	131	86	
Green	1,071	265	118	70	
Blue	532	134	59	36	
Indigo	163	40	18	11	
Lime	1,970	487	217	128	
Full	4,850	1,189	533	316	
Diameter	Ø1.53m / 5'0"	Ø2.14m / 10'0"	Ø3.22m / 15'1"	Ø4.29m / 20'1"	

