



F200FCMZ

200W RGBL FRESNEL



Photometrics	F200FCMZ
Light Source	200 W RGBL (RGB, Lime) LED Module, CRI: 90+
Beam Angle	14°~55°
Output	3,470 lux @ 2.5 m @ 14°
Lens	150 mm Fresnel
PWM	1,000-16,000 Hz, adjustable
LED Lifespan	50,000 hours
Effects	
Dimming	0~100%, 8-bit / 16-bit
Strobe	1~25 Hz
Zoom	Manual 14°~55°
Power	
Input Voltage	100~240 V AC, 50/60 Hz, 200 W
Connection	NEUTRIK® powerCON in/out
Control	
Operation Modes	DMX, manual, master/slave
Control Protocol	DMX512
DMX Channels	7/8/13/8H/9H
Control Interface	3-pin XLR (optional: 5-pin XLR)
Display	4-button LCD control panel
Housing	
Housing Materials	Aluminium and ABS, matte black finish
Cooling	Sensor thermostat controlled variable speed fan
IP Rating	IP20
Net Weight	5.5 kg
Accessories	
Included	Barn door, gel frame



F200FCMZ LUX CHART

Lux				Lux			
	2.5m	5.0m	7.5m		2.5m	5.0m	7.5m
	@ 14°				@ 55°		
	Ø0.70	Ø1.41	Ø2.11		Ø1.11	Ø2.22	Ø3.33
R	516	129	57	R	295	74	33
G	1,040	260	116	G	552	138	61
B	1,680	420	187	B	853	213	95
L	1,215	304	135	L	662	166	74
Full	3,470	868	386	Full	1,766	442	196

