

TSUNAMI2-IP

OUTDOOR 28 / 14 SEGMENT LED TILT MOVING HEAD PANEL









160-1	744444	
•		

Photometrics	Strobe: 392pcs White 1.5W LEDs	
	Surface effect: 784pcs RGB 0.8W RGB 3in1 LEDs	
	Beam angle: 117°	
	Output: 72,600 Lm	
	Colour rendering index: RA≥80	
	Life: 50,000 hour	
Power rating	Strobe power: 1,250W	
	Rated power: 720W	
Effect	RGBW color mixing system	
	Pixel control: 28-segment strobe, 14-segment colour RGB	
	Refresh frequency: >25KHz camera image is flicker-free	
	Dimming: 0-100% linear dimming; 4 dimming modes	
	Strobe: 0.5-20 Hz	
	Vertical scanning: 180°	
Control	DMX512, Art-Net, RDM	
	DMX Channels: 8 / 11 / 13 / 24 / 30 /74 / 97	
	Display: TFT, 4 - button control	
Interface:	DMX: 5-pin in / out	
	Art-net: RJ45 in / out	
Other functions	X axis, Y axis fine tuning	
Housing	High strength casting aluminum alloy, black	
	Working temperature: -10°C ~ 45°C	
	IP rating: IP65	
	Dimensions: 494x316x160mm	
	Weight: 15Kg	



Lux	3m	5m
R	341	156
G	965	427
В	175	76
RGB	846	361
w	3,139	1,753
RGBW (Full)	3,748	1,588



1 x omega bracket with 1/4 - turn quick locks



